

TURTLE WAX, INC. 625 WILLOWBROOK CTR PKWY WILLOWBROOK, IL 60527

SAFETY DATA SHEET

1. Product and Company Identification

1.1 Product Identifier

Product Name: Turtle Wax Power Foam Bug & Tar (Aerosol)

Product Code (SKU): 50595 (US), 50605 (CAN)

1.2 Relevant Identified Uses Of The Substance

Product Use: Bug & Tar Remover

1.3 Details of the Supplier of the SDS

Company Name: Turtle Wax, Inc.

Street Address: 625 Willowbrook Centre Parkway City, State, Zip Code: Willowbrook, Illinois 60527

1.4 Emergency Telephone Numbers

Phone Number: 1(630)455-3700 Fax Number: 1(630)455-3868

Transportation: 1(800)424-9300 (CHEMTREC)
Medical Assistance: Call your local Poison Control Center

2. <u>Hazard Identification:</u>

2.1 Classification of the Substance or Mixture

Hazard Classification: Gas Under Pressure – Liquified Gas

Acute Toxic 4 (Inhalation) Flammable Aerosol 2 Skin Irritation 2 Eye Irritation 2B

2.2 Label Elements

Pictogram:

Signal Word: Warning

Hazard Statement: Contains gas under pressure; May explode if heated.

Flammable Aerosol. Harmful if inhaled. Causes skin and

eye irritation.

Precautionary Statement: Keep away from heat, sparks, hot surfaces or open flames.

Do not smoke or spray near open flame or source of ignition. Pressurized container: Do not puncture or incinerate. Avoid breathing fumes, gas, or vapors. Use in well ventilated area. Wash hands thoroughly after use. Remove contaminated clothing and launder before re-use.

If in eyes, rinse thoroughly with water for 15 minutes. Remove contact lenses if possible. If eye or skin irritation persists, seek medical attention. Do not store in direct sunlight or at temperatures above 50°C (122°F). Store in a well ventilated place.

2.3 Other Hazards

Description of additional HNOC: Intentional misuse by deliberately concentrating and inhaling

the contents may be harmful or fatal.

3. Information on Ingredients:

3.1 Substance not applicable

3.2 Mixture

Component	CAS Number	Concentration (wt%)
Water	7732-18-5	>80%
Petroleum Distillates	64742-47-8	20-30%
Propane	74-98-6	1 – 3%
Isobutane	75-28-5	1 – 3%
Sodium Lauryl Sulfate	151-21-3	1 – 5%
Sodium Lauroyl Sarcosinate	137-16-6	0.5 – 1.5%

4. First Aid Measures:

4.1 Description of First Aid Measures

Inhalation: Remove to fresh air and promote deep breathing. Get medical attention if effects persist.

Skin: In case of skin contact, wash thoroughly with soap and water. If irritation persists, get medical attention.

Eyes: In case of eye contact, immediately flush eyes with plenty of water. Remove contact lenses if worn. If irritation persists, get medical attention

Ingestion: If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. Give water to drink if conscious. Get medical attention if effects persist.

4.2 Most important symptoms and effects – acute and chronic

Inhalation: May cause respiratory tract irritation.

Skin: May cause skin irritation. May cause drying, cracking, or mild dermatitis. **Eyes:** May cause temporary eye irritation. Symptoms may include excess

blinking and tearing.

Ingestion: May cause stomach distress, nausea, and vomiting.

4.3 Indication of any immediate medical attention and special treatment

Symptoms may not appear immediately. Seek medical attention if effects persist and you feel unwell.

5. Fire Fighting Measures:

5.1 Extinguishing media

Water spray, carbon dioxide, dry chemical, and alcohol foam

5.2 Special hazards arising from the substance or mixture

CO₂, CO, and hydrocarbons

5.3 Advice for Fire Fighters

Keep up wind of fire. Wear full firefighting turn out gear (full bunker gear) and respiratory protection (SCBA). See Section 8 for personal protection.

6. Accidental Release Measures:

6.1 Personal precautions, protective equipment, and emergency procedures

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.2 Methods and materials for containment and clean up

For containment: Contain and absorb spill with inert material. Place in suitable container for disposal. Spilled material may be slippery.

For clean up: Take up material and place in a suitable container. Provide adequate ventilation. Spilled material may be slippery.

7. Handling and Storage

7.1 Precautions for safe handling

Avoid contact with skin and eyes. Do not swallow. Do not eat, drink or smoke while handling. Wash hands with soap and water after handling. Launder all clothing and foot wear before reuse.

7.2 Conditions for safe storage including incompatibilities

Keep out of reach of children. Store in a well ventilated place. Do not store above 49°C (120°F).

7.3 Specific end uses

Shelf Life: Shelf life is considered to be 7 - 10 years when properly stored. Aerosol products have been known to last much longer in storage.

8. Exposure Control/Personal Protection:

8.1 Control parameters

Exposure Limits 8 hr TWA:	<u>(OSHA PEL)</u>	(ACGIH TWA)
Petroleum Distillates (64742-47-8)	500 ppm	100 ppm
Propane	1000 ppm	1000 ppm
Isobutane	not available	1000 ppm
Sodium Lauryl Sulfate	not applicable	not applicable
Sodium Lauroyl Sarcosinate	not applicable	not applicable

8.2 Exposure controls

Use adequate ventilation to keep exposure below recommended limits. Ensure that eye wash station and safety shower are close to work station.

Hand Protection Equipment: Wear chemical resistant gloves and clothing to prevent skin contact.

Eye Protection Equipment: Wear safety glasses or splash goggles to prevent eye contact.

Skin and Body Protection: Wear suitable protective clothing.

Respiration/Ventilation Protection Requirements: Provide good ventilation.

Ingestion Protection Requirements: Do not eat, drink or smoke while handling. Wash hands

with soap and water after handling. Launder all clothing and foot wear before re-use.

9. Physical And Chemical Properties:

9.1 Information of basic chemical and physical properties

Physical Form: Gas/Pressurized Liquid

Color: Clear Thin Liquid (Dispensed as white foam)

Odor: Typical solvent Odor Threshold: Typical solvent not available

pH: not applicable – oil out emulsion

Melting Point/Freeze Point: 0°C (32°F) – Based on Water (liquid phase) Initial Boiling Point: 100°C (212°F) – Based on Water (liquid phase)

Flash Point (Seta Closed Cup): not available

Flammability Limits: Explosive Limits: Upper: not available Lower: not available

Evaporation Rate:not availableFlammability Solid/Gas:not applicableVapor Pressure:not availableVapor Density:not available

Specific Gravity: 1.000 (liquid phase)

Solubility in Water: insoluble Auto Ignition Temperature: not available Partition coefficient (n/octonol/water): not available

Viscosity: Water Thin (liquid phase)

9. 2 Other information

% NVM by Weight: 5.5% % VOC Content (California): 37.5%

10. Stability and Reactivity:

10.1 Reactivity

Does not react under normal conditions

10.2 Chemical stability

Stable

10.3 Possibility of hazardous reactions

Does not react under normal conditions

10.4 Conditions to avoid

Heat and incompatible materials

10.5 Incompatible materials

Strong oxidizers such as bleach and peroxides

10.6 Hazardous decomposition products

CO₂, CO and hydrocarbons

11. Toxicological Information:

11.1 Information on Toxicological effects

Turtle Wax Power Foam Bug & Tar (Aerosol)

LD50 – Oral Rat >2000 mg/Kg LD50 – Dermal Rabbit >2000 mg/Kg LC50 – Inhalation Rat >3.81 mg/L (4 hr)

Petroleum Distillates - Mineral Spirits (64742-47-8)

LD50 – Oral Rat >5000 mg/Kg LD50 – Dermal Rabbit >2000 mg/Kg LC50 – Inhalation Rat >20 mg/L 1h

Isobutane (75-28-5)

LC50 – Inhalation Rat 658 mg/L (4hr)

Sodium Lauryl Sulfate (151-21-3)

LD50 – Oral Rat 1288 mg/Kg LD50 – Dermal Rabbit 580 mg/Kg

LC50 – Inhalation Rat >3900 mg/m³ (1 hr)

Propane (76-98-6)

LD50 – Inhalation Rat 658 mg/L(4hr)

Sodium Lauroyl Sarcosinate (137-16-6)

LD50 – Oral Rat >5000 mg/Kg LC50 – Inhalation Rat 0.05-0.5 mg/L (4 hr)

Skin corrosion/irritation
Serious eye damage/irritation
Can cause mild skin irritation
Can cause mild eye irritation

Respiratory or skin sensitization
Germ cell mutagenicity
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met
Based on available data, classification data are not met

Specific target organs – single exposure

Based on available data, classification data are not met

Specific target organs - repeated exposure

Aspiration hazard Based on available data, classification data are not met Based on available data, classification data are not met Harmful if inhaled. May cause respiratory tract irritation.

Intentional misuse by deliberately concentrating and inhaling

the contents may be harmful or fatal.

Symptoms/injuries after skin contact May cause skin irritation. May cause drying, cracking, or

mild dermatitis.

Symptoms/injuries after eye contact May cause temporary eye irritation. Symptoms may include

discomfort, excess blinking, and tearing.

Symptoms/injuries after ingestion May be harmful if swallowed. May cause stomach distress,

nausea, and vomiting.

12. Ecological Information:

12.1 Toxicity

Not recommended for release into aquatic systems without treatment

12.2 Persistence and degradability

Not established

12.3 Bioaccumulative potential

Not established

12.4 Mobility in soil

Not established

12.5 Other adverse effects

None known

13. <u>Disposal Considerations</u>:

13.1 Waste treatment methods

RCRA Hazardous Waste: Regulated as a hazardous waste (D-001 Ignitable).

Waste Disposal Method: Dispose of in accordance with local, state and federal

regulations

Waste Disposal Vessel: Metal drums are recommended. Dispose of un-used

aerosol cans through a registered aerosol recycler.

14. <u>Transportation Information</u>:

14.1 UN number

1950

14.2 UN Proper shipping name

Aerosol - Flammable

14.3 Transport Hazard class

2.1 Flammable Gas

14.4 Packaging group

Not applicable

14.5 Marine Pollutant

No

14.6 Transportation in Bulk

Not applicable

14.7 Special precautions

NFPA (34b) Level 2 Aerosol

15. Regulatory Information:

15.1 US Federal Regulations

TSCA Status: All ingredients are commercially available and listed by the manufacturer under TSCA.

15.2 Foreign Regulations

Canadian Status: All materials contained in this product are listed on the Canadian Domestic Substance List (DSL). Consult Turtle Wax, Inc. regarding status of ingredients.

European Union: All materials contained in this product are listed on EINECS.

AICS: All materials are registered for AICS (Australia)

15.3 State Regulations

State Regulatory Information:

The following chemicals are specifically listed by individual states; other product specific health and safety data in other sections of the SDS may also be applicable for state requirements. For details on your regulatory requirements, contact the appropriate agency in your state.

California Prop 65:

CAS Number	<u>Concentration</u>	State Code
None		

15.4 HIMS & NFPA Classifications

HIMS Classification:	Health Flammability Reactivity	2 2 0
NFPA Classification:	Health Flammability Reactivity	2 2 0

16. Other Information:

Reason For Issue Conversion to OSHA GHS SDS Format

Prepared By James Heidel - Consultant

Preparer's Title Technical Director, R&D

SDS Administrator Jean Mayszak - Technical Compliance Manager, R&D

Approval Date August 6, 2015

Supersedes DateNewRevision NumberA-0

This information is, to the best of Turtle Wax, Inc.'s knowledge and belief, accurate and reliable. However, no representation, warranty, or guarantee is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy oneself as to the suitableness and completeness of such information for their own particular use.