

Material Name: PROPANE SDS ID: MAT19690

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

PROPANE

Synonyms

MTG MSDS 76; N-PROPANE; DIMETHYLMETHANE; PROPYL HYDRIDE; R-

290; PROPYLHYDRIDE; LIQUEFIED PETROLEUM GAS; LPG; >96% NATURAL GRADE; >99.9%

PURE GRADE; UN 1978; C3H8

Chemical Family

Hydrocarbons, aliphatic

Product Use

Industrial and Specialty Gas Applications.

Restrictions on Use

None known.

Details of the supplier of the safety data sheet

MATHESON TRI-GAS, INC. 150 Allen Road, Suite 302

Basking Ridge, NJ 07920

General Information: 1-800-416-2505

Emergency #: 1-800-424-9300 (CHEMTREC) Outside the US: 703-527-3887 (Call collect)

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Gases - Category 1

Gases Under Pressure - Liquefied gas

Specific target organ toxicity - Single exposure - Category 3

GHS Label Elements

Symbol(s)



Signal Word Danger

Page 1 of 10 Issue date: 2015-12-10 Revision 2.3 Print date: 2015-12-10



Material Name: PROPANE SDS ID: MAT19690

Hazard Statement(s)

Extremely flammable gas.

Contains gas under pressure; may explode if heated.

May cause drowsiness and dizziness.

May displace oxygen and cause rapid suffocation.

Precautionary Statement(s)

Prevention

Keep away from heat, sparks, open flame, and hot surfaces - No smoking.

Avoid breathing gas.

Use only outdoors or in a well-ventilated area.

Response

Leaking gas fire.

Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

IF INHALED.

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Storage

Store in a well-ventilated place.

Protect from sunlight.

Keep container tightly closed.

Store locked up.

Disposal

Dispose in accordance with all applicable regulations.

Other Hazards

May cause frostbite upon sudden release of liquefied gas.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent		
74-98-6	Propane	>96		

Section 4 - FIRST AID MEASURES

Inhalation

If adverse effects occur, remove to uncontaminated area. Give artificial respiration if not breathing. If breathing is difficult, oxygen should be administered by qualified personnel. Get immediate medical attention.

Page 2 of 10 Issue date: 2015-12-10 Revision 2.3 Print date: 2015-12-10



Material Name: PROPANE SDS ID: MAT19690

Skin

If frostbite or freezing occur, immediately flush with plenty of lukewarm water (105-115 F; 41-46 C). DO NOT USE HOT WATER. If warm water is not available, gently wrap affected parts in blankets. Get immediate medical attention.

Eyes

Immediately flush eyes with plenty of water for at least 15 minutes. Then get immediate medical attention.

Ingestion

If swallowed, get medical attention.

Most Important Symptoms/Effects

Acute

frostbite, suffocation, central nervous system depression

Delayed

no information on significant adverse effects.

Note to Physicians

For inhalation, consider oxygen.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

regular dry chemical, carbon dioxide, Large fires: water spray or fog

Unsuitable Extinguishing Media

Do not direct water at source of leak or safety devices; icing may occur.

Special Hazards Arising from the Chemical

Severe fire hazard. Severe explosion hazard. Gas/air mixtures are explosive. The vapor is heavier than air. Vapors or gases may ignite at distant ignition sources and flash back. Electrostatic discharges may be generated by flow or agitation resulting in ignition or explosion.

Hazardous Combustion Products

Oxides of carbon

Fire Fighting Measures

Move container from fire area if it can be done without risk. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. For tank, rail car or tank truck: Stop leak if possible without personal risk. Let burn unless leak can be stopped immediately. For smaller tanks or cylinders, extinguish and isolate from other flammables. Evacuation radius: 800 meters (1/2 mile). Stop flow of gas.

Page 3 of 10 Issue date: 2015-12-10 Revision 2.3 Print date: 2015-12-10



Material Name: PROPANE SDS ID: MAT19690

Special Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Avoid heat, flames, sparks and other sources of ignition. All equipment used when handling the product must be grounded. Remove sources of ignition. Do not touch or walk through spilled material. Stop leak if possible without personal risk. If possible, turn leaking containers so that gas escapes rather than liquid. Use water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to contact spilled material. Do not direct water at spill or source of leak. Keep unnecessary people away, isolate hazard area and deny entry. Ventilate closed spaces before entering.

Environmental Precautions

Avoid release to the environment.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash hands thoroughly after handling.

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place.

Protect from sunlight.

Keep container tightly closed.

Store locked up.

Store and handle in accordance with all current regulations and standards. Protect from sunlight. Store in a well-ventilated area. Keep container tightly closed. Grounding and bonding required. Keep locked up. Subject to storage regulations: U.S. OSHA 29 CFR 1910.110. Keep separated from incompatible substances.

Incompatible Materials

combustible materials, oxidizing materials

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Page 4 of 10 Issue date: 2015-12-10 Revision 2.3 Print date: 2015-12-10



Material Name: PROPANE SDS ID: MAT19690

Propane	74-98-6
ACGIH:	(See Appendix F: Minimal Oxygen Content)
NIOSH:	1000 ppm TWA; 1800 mg/m3 TWA
	2100 ppm IDLH (10% LEL)
OSHA (US):	1000 ppm TWA; 1800 mg/m3 TWA

EU - Occupational Exposure (98/24/EC) - Binding Biological Limit Values and Health Surveillance Measures

There are no biological limit values for any of this product's components.

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

For the gas: Eye protection not required, but recommended. For the liquid: Wear splash resistant safety goggles. Contact lenses should not be worn. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

For the gas: Protective clothing is not required. For the liquid: Wear appropriate protective, cold insulating clothing.

Respiratory Protection

The following respirators and maximum use concentrations are drawn from NIOSH and/or OSHA. 2100 ppm. Any supplied-air respirator. Any self-contained breathing apparatus with a full facepiece. Emergency or planned entry into unknown concentrations or IDLH conditions -. Any self-contained breathing apparatus that has a full facepiece and is operated in a pressure-demand or other positive-pressure mode. Any supplied-air respirator with a full facepiece that is operated in a pressure-demand or other positive-pressure mode in combination with an auxiliary self-contained breathing apparatus operated in pressure-demand or other positive-pressure mode. Escape -. Any appropriate escape-type, self-contained breathing apparatus.

Glove Recommendations

Wear insulated gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	colorless gas	Physical State	gas	
Odor	gasoline odor	Color	colorless	

Page 5 of 10 Issue date: 2015-12-10 Revision 2.3 Print date: 2015-12-10



Material Name: PROPANE SDS ID: MAT19690

Odor Threshold	5000 - 20000 ppm	pН	Not available	
Melting Point	-190 °C (-310 °F)	Boiling Point	-40 °C (-40 °F)	
Freezing point	Not available	Evaporation Rate	Not available	
Boiling Point Range	Not available	Flammability (solid, gas)	Flammable gas	
Autoignition	450 °C (842 °F)	Flash Point	-105 °C (-157 °F)	
Lower Explosive Limit	2.1 %	Decomposition	Not available	
Upper Explosive Limit	9.5 %	Vapor Pressure	6398 mmHg at 21.1 °C	
Vapor Density (air=1)	1.55	Specific Gravity (water=1)	0.5853 at -45 °C	
Water Solubility	(Very slightly soluble)	Partition coefficient: n-octanol/water	Not available	
Viscosity	Not available	Solubility (Other)	Not available	
Density	Not available	Log KOW	2.36	
Physical Form	gas	Molecular Formula	С-Н3-С-Н2-С-Н3	
Molecular Weight	44.11			

Solvent Solubility

Soluble

absolute alcohol, ether, chloroform, Benzene, turpentine

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid heat, flames, sparks and other sources of ignition. Minimize contact with material. Containers may rupture or explode if exposed to heat.

Page 6 of 10 Issue date: 2015-12-10 Revision 2.3 Print date: 2015-12-10



Material Name: PROPANE SDS ID: MAT19690

Incompatible Materials

combustible materials, oxidizing materials

Hazardous decomposition products

Oxides of carbon

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

nausea, vomiting, irregular heartbeat, headache, drowsiness, dizziness, Disorientation, mood swings, loss of coordination, suffocation, convulsions, Unconsciousness, coma

Skin Contact

blisters, frostbite

Eye Contact

frostbite, blurred vision

Ingestion

ingestion of a gas is unlikely

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Propane (74-98-6)

Inhalation LC50 Rat 658 mg/L 4 h

Immediate Effects

frostbite, suffocation, central nervous system depression

Delayed Effects

no information on significant adverse effects.

Irritation/Corrosivity Data

No data available.

Respiratory Sensitization

No data available.

Dermal Sensitization

No data available.

Component Carcinogenicity

None of this product's components are listed by ACGIH, IARC, NTP, DFG or OSHA

Germ Cell Mutagenicity

No data available.

Page 7 of 10 Issue date: 2015-12-10 Revision 2.3 Print date: 2015-12-10



Material Name: PROPANE SDS ID: MAT19690

Tumorigenic DataNo data available

Reproductive Toxicity

No data available.

Specific Target Organ Toxicity - Single Exposure

central nervous system

Specific Target Organ Toxicity - Repeated Exposure

No target organs identified.

Aspiration hazard

Not applicable.

Medical Conditions Aggravated by Exposure

None known.

Additional Data

Stimulants such as epinephrine may induce ventricular fibrillation.

Section 12 - ECOLOGICAL INFORMATION

Component Analysis - Aquatic Toxicity

No LOLI ecotoxicity data are available for this product's components

Persistence and Degradability

This material is expected to biodegrade.

Bioaccumulative Potential

Bioconcentration potential in aquatic organisms is low based on a BCF value of 13.

Mobility

Expected to have moderate mobility in soil.

Other Toxicity

No additional information is available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.

Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components

Page 8 of 10 Issue date: 2015-12-10 Revision 2.3 Print date: 2015-12-10



Material Name: PROPANE SDS ID: MAT19690

Section 14 - TRANSPORT INFORMATION

US DOT Information: Shipping Name:Propane Hazard Class: 2.1

Hazard Class: 2.1 UN/NA #: UN1978 Required Label(s): 2.1

IMDG Information: Shipping Name:Propane

Hazard Class: 2.1 UN#: UN1978

Required Label(s): 2.1

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

None of this products components are listed under SARA Sections 302/304 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan.

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: No Fire: Yes Pressure: Yes Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Propane	74-98-6	No	Yes	Yes	Yes	Yes

Not listed under California Proposition 65

Canadian WHMIS Ingredient Disclosure List (IDL)

The components of this product are either not listed on the IDL or are present below the threshold limit listed on the IDL.

WHMIS Classification

A., B1.

Component Analysis - Inventory

Propane (74-98-6)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX	TW
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes	Yes

Page 9 of 10 Issue date: 2015-12-10 Revision 2.3 Print date: 2015-12-10



Material Name: PROPANE SDS ID: MAT19690

Section 16 - OTHER INFORMATION

NFPA Ratings

Health: 2 Fire: 4 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes Updated: 05/01/2015

Key/Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

Matheson Tri-Gas, Inc. makes no express or implied warranties, guarantees or representations regarding the product or the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Matheson Tri-Gas, Inc. shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.

Page 10 of 10 Issue date: 2015-12-10 Revision 2.3 Print date: 2015-12-10