

Product Safety Data Sheet

XEROX

Product: Document Centre 535/545/555 DC and ST

PSDS No.: 0880

ISSUE DATE: 07/24/02

REV. DATE:

Section I - Product Identification

Manufacturer's Name

Xerox Corporation

Emergency No.

(585) 422-2177

EH&S Inquiries

(800) 828-6571

Manufacturer's Address

Rochester, N.Y.

Product Designation

Document Centre 535/545/555 DC and ST

Product Identifier:

XEW1

Section II - Electrical Information

Line Voltage

(Volts)

110 - 127

Line Current

(Amps)

12.0

Freq.

(Hertz)

60

Branch Cir. Protection

(Amps)

15

Line Cord/Plug Specification

Provided with Appliance coupler

Detachable Cord, Two wire + Ground

NEMA 5-15P

Power Consumption (Watts)*

	555		545		535		+LCSS
	DC	ST	DC	ST	DC	ST	
Running (Average)	1200	1250	1200	1250	1150	1150	65
Standby	235	290	235	290	190	250	10
Low Power	125	145	125	145	110	130	0
Sleep Mode	45	65	45	65	45	65	0
Standby Off Mode	3	3	3	3	3	3	0

The main appliance coupler of this equipment is the power disconnect device

Agency Approval

UL File Number E153709

cUL File Number E153709

Section III - Supplies

Toner Replenisher Cartridge

Xerox Part No.

6R1046 / 6R1047

Material Safety Data Sheet

A34

Section IV - Environmental Information

Product Size

(mm)

DC/ST Fully Configured

D: 635

W: 1346

H: 1115

Heat Emission*

(BTU) Max

Based on 55 ST

Running: 3,750

Standby: 870

Low Power: 435

Sleep: 195

Environmental Limitations

Min Max

Relative Humidity (%) 10 85

Ambient Temp. (°C) 10 32

*Note: Heat emission (Btu) for all other configurations should be calculated based Watts x 3

Floor Space Requirements

(mm)
DC/ST Fully Configured
W: 2,809
D: 1,575

Weight

(K Grams)
Fully Configured: 181

Section V - Emission/Exposure Information***Light Sources**

Scanner lamp is rare gas Fluorescent.
To avoid discomfort the lamp should not
be directly viewed.
Class I Laser Product

Accession #

0120666-00

Electromagnetic Emissions

US FCC: Class A
Canada DOC: Class A

Audible Noise (DC Platen copying.
No output device)

TLV

	555	545	535
Run	68 dB(A)	67dB(A)	65dB(A)
Standby	47 dB(A)	47dB(A)	46dB(A)
Impulse	71 dB(A)	70dB(A)	70dB(A)

85.0 dB(A)

Audible Noise Fully Configured (ST/DC

Document Handler and output device)

Maximum Values

	555	545	535
Run	78dB(A)	75dB(A)	75dB(A)
Standby	47	47	47
Impulse	83dB(A)	80dB(A)	80dB(A)

85.0 dB(A)

Ozone

0.005 ppm

Peak value based on 2 hours continuous operation
in test chamber 50m3.

TLV

0.1 ppm

Total Dust

0.02mg/m3

TWA over 4 hours of continuous operation in
standard test chamber 50m3.

TLV

10 mg/m

VOC's

Insignificant quantities detected (<0.1ppm)
during 1 hour of continuous operation.

Section VI - Product Recycling and Disposal

Xerox operates a worldwide equipment takeback and reuse/recycle program. Contact your Xerox sales representative (1-800-ASK-XEROX) to determine whether this Xerox product is part of the program. For more information about Xerox environmental programs, visit www.xerox.com (refer to "About Xerox" section). If your product is not part of the Xerox program and you are managing its disposal, please note that the product may contain lead, mercury and other materials whose disposal may be regulated due to environmental considerations. For recycling and disposal information, contact your local authorities. In the United States, you may also refer to the Electronic Industries Alliance web site: www.eiae.org.