

Printing date: 03/23/2016

Revision: 03/23/2016

1 Identification
· Product identifier
 Trade name: <u>Roof Mastic- Rain Kote</u> Product code: RKM4: 1 Gallon Roof Mastic Asbestos Free RKM10: 10.3 oz. Roof Mastic Asbestos Free-Cartridge RKM1: 1 Quart Roof Mastic Asbestos Free
 Recommended use and restriction on use Recommended use: Roof coating Restrictions on use: No relevant information available.
 Details of the supplier of the Safety Data Sheet Manufacturer/Supplier: L.H. Dottie Company 6131 Garfield Ave. Commerce, CA 90040 (323) 725-1000
 Emergency telephone number: ChemTel Inc. +1 (800)255-3924, +1 (813)248-0585
2 Hazard(s) identification
Classification of the substance or mixture
Flam. Liq. 3 H226 Flammable liquid and vapor.
Muta. 1B H340 May cause genetic defects.
Carc. 1B H350 May cause cancer.
STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.
 Label elements GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms:
GHS02 GHS08
· Signal word: Danger
 Hazard-determining components of labeling: Asphalt Stoddard solvent Attapulgite (Palygorskite) Hazard statements: H226 Flammable liquid and vapor. H340 May cause genetic defects. H350 May cause cancer.
(Cont'd. on page 2)



Printing date: 03/23/2016

Revision: 03/23/2016

Trade name: Roof Mastic- Rain Kote		
	(Cont'd. of page 1)	
	amage to the central nervous system through prolonged or repeated exposure.	
• Precautionary s		
P201	Obtain special instructions before use.	
P202	Do not handle until all safety precautions have been read and understood.	
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.	
P241	Use explosion-proof electrical/ventilating/lighting/equipment.	
P260	Do not breathe mist/vapors/spray.	
P264	Wash thoroughly after handling.	
P280	Wear protective gloves and eye protection.	
P240	Ground/bond container and receiving equipment.	
P233	Keep container tightly closed.	
P242	Use only non-sparking tools.	
P243	Take precautionary measures against static discharge.	
P270	Do not eat, drink or smoke when using this product.	
P303+P361+P3	53 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
P370+P378	In case of fire: Use foam, powder, or carbon dioxide for extinction.	
P331	Do NOT induce vomiting.	
P308+P313	IF exposed or concerned: Get medical advice/attention.	
P405	Store locked up.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.	
[•] Other hazards	There are no other hazards not otherwise classified that have been identified.	

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Component	ts:	
8052-42-4	Asphalt	40-60%
	🗞 Carc. 2, H351	
8052-41-3	Stoddard solvent	10-20%
	 Flam. Liq. 3, H226 Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304 	
1332-58-7	Kaolin	10-20%
12174-11-7	Attapulgite (Palygorskite)	<10%
	🗞 Carc. 2, H351	
9004-34-6	Cellulose	<5%
· Additional i	nformation:	

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements refer to section 16.

(Cont'd. on page 3)





acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/23/2016

Revision: 03/23/2016

Trade name: Roof Mastic- Rain Kote

(Cont'd. of page 2)

D	Description of first aid measures
A	fter inhalation:
	upply fresh air; consult doctor in case of complaints.
Ρ	rovide oxygen treatment if affected person has difficulty breathing.
	fter skin contact:
	o not pull solidified product away from the skin.
	Vash with soap and water.
	skin irritation is experienced, consult a doctor.
	fter eye contact:
	temove contact lenses if worn.
	tinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
	fter swallowing:
	tinse out mouth and then drink plenty of water.
	o not induce vomiting; immediately call for medical help.
	lost important symptoms and effects, both acute and delayed:
	leadache
	reathing difficulty
_	Vizziness
	light irritant effect on skin and mucous membranes.
	light irritant effect on eyes.
	Bastric or intestinal disorders when ingested. lausea in case of ingestion.
	Inconsciousness
_	langer:
	langer of impaired breathing.
	lay cause genetic defects.
	lay cause cancer.
	Causes damage to the central nervous system through prolonged or repeated exposure.
	indication of any immediate medical attention and special treatment needed:
	ledical supervision for at least 48 hours.
	necessary oxygen respiration treatment.

Extinguishing media Suitable extinguishing agents: Water fog / haze Foam Gaseous extinguishing agents Fire-extinguishing powder Carbon dioxide For safety reasons unsuitable extinguishing agents: Water stream. Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

(Cont'd. on page 4)



acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/23/2016

Revision: 03/23/2016

Trade name: Roof Mastic- Rain Kote

(Cont'd. of page 3)

Advice for firefighters

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information:

Eliminate all ignition sources if safe to do so. Cool endangered containers with water fog.

6 Accidental release measures

[•] Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

Protect from heat.

Particular danger of slipping on leaked/spilled product.

Environmental precautions: Avoid release to the environment.

Methods and material for containment and cleaning up:

Allow to solidify. Pick up mechanically.

Send for recovery or disposal in suitable receptacles.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling · Precautions for safe handling: Prevent formation of aerosols. Use only in well ventilated areas. · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available. Flammable gas-air mixtures may be formed in empty containers/receptacles. Conditions for safe storage, including any incompatibilities · Storage · Requirements to be met by storerooms and receptacles: Provide ventilation for receptacles. Avoid storage near extreme heat, ignition sources or open flame. · Information about storage in one common storage facility: Store away from foodstuffs.

Store away from oxidizing agents.

(Cont'd. on page 5)



Printing date: 03/23/2016

Revision: 03/23/2016

Trade name: Roof Mastic- Rain Kote

(Cont'd. of page 4)

· Further information about storage conditions:

Keep containers tightly sealed. Protect from heat and direct sunlight.

• Specific end use(s): No relevant information available.

8 Exposure co	Exposure controls/personal protection		
[.] Control paran	neters		
Components w	vith limit values that require monitoring at the workplace:		
8052-42-4 Asph	nalt		
REL (USA)	Ceiling limit value: 5* mg/m³ *15-min; See Pocket Guide App. A		
TLV (USA)	Long-term value: 0.5* mg/m³ *inh. fraction; as benzene-soluble aerosol; BEIp		
EL (Canada)	Long-term value: 0.5 mg/m³ inhalable, IARC 2B		
EV (Canada)	Long-term value: 0.5 mg/m ³ fume, as benzene-soluble aerosol, inhalable		
LMPE (Mexico)	Long-term value: 0.5* mg/m³ A4, IBEp;*fracción inhalable		
8052-41-3 Stod	dard solvent		
PEL (USA)	Long-term value: 2900 mg/m ³ , 500 ppm		
REL (USA)	Long-term value: 350 mg/m³ Ceiling limit value: 1800* mg/m³ *15-min		
TLV (USA)	Long-term value: 525 mg/m ³ , 100 ppm		
EL (Canada)	Short-term value: 580 mg/m³ Long-term value: 290 mg/m³		
EV (Canada)	Long-term value: 525 mg/m ³		
LMPE (Mexico)	Long-term value: 100 ppm		
1332-58-7 Kaol	in		
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction		
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction		
TLV (USA)	Long-term value: 2* mg/m³ E; as respirable fraction		
EL (Canada)	Long-term value: 2 mg/m ³		
EV (Canada)	Long-term value: 2(D) mg/m ³ respirable		
LMPE (Mexico)	Long-term value: 2* mg/m³ A4, *fracción respirable		
	(Cont'd. on p	age	





acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/23/2016

Trade name: Roof Mastic- Rain Kote

Revision: 03/23/2016

(Cont'd. of page 5) 9004-34-6 Cellulose PEL (USA) Long-term value: 15* 5** mg/m³ *total dust **respirable fraction Long-term value: 10* 5** mg/m³ REL (USA) *total dust **respirable fraction TLV (USA) Long-term value: 10 mg/m³ Long-term value: 10* 3** mg/m³ EL (Canada) *total dust, **respirable fraction Long-term value: 10 mg/m³ EV (Canada) paper fibre, total dust LMPE (Mexico) Long-term value: 10 mg/m³ · Ingredients with biological limit values: 8052-42-4 Asphalt BEI (USA) Medium: urine Time: end of shift at end of workweek Parameter: 1-Hydroxypyrene with hydrolysis (nonguantitative) • Exposure controls · Personal protective equipment: General protective and hygienic measures: The usual precautionary measures for handling chemicals should be followed. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Engineering controls: No relevant information available. · Breathing equipment: Not required under normal conditions of use. For spills, respiratory protection may be advisable. NIOSH or EN approved organic vapor respirator equipped with a dust/mist prefilter should be used. Protection of hands: Gloves are advised for repeated or prolonged contact. Wear protective gloves to handle contents of damaged or leaking units. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. • Eye protection: Follow relevant national guidelines concerning the use of protective eyewear. · **Body protection:** Protective work clothing · Limitation and supervision of exposure into the environment No relevant information available. Risk management measures No relevant information available.

(Cont'd. on page 7)



Printing date: 03/23/2016

Revision: 03/23/2016

Trade name: Roof Mastic- Rain Kote

(Cont'd. of page 6)

9 Physical and chemical prope	rties
· Information on basic physical a	nd chemical properties
· Appearance:	
Form:	Liquid
Color:	Black
· Odor:	Petroleum-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
Melting point/Melting range:	Not determined.
 Boiling point/Boiling range: 	>149 °C (>300 °F)
· Flash point:	41 °C (106 °F)
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not self-igniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
 Oxidizing properties: 	Not determined.
· Vapor pressure at 20 °C (68 °F):	0.293 kPa
· Density:	1.02 - 1.12 g/cm³ (8.512 - 9.346 lbs/gal)
· Relative density:	Not determined.
· Vapor density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
·Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
VOC content:	<250 g/l
[•] Other information	No relevant information available.

10 Stability and reactivity

Reactivity: No relevant information available.
 Chemical stability: Stable under normal temperatures and pressures.

(Cont'd. on page 8)



Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/23/2016

Revision: 03/23/2016

of Mastic- Rain Kote Trado namo: D

Trade name: Roof Mastic- Rain Kote	
 Thermal decomposition / conditions to be avoided: Keep away from heat and direct set Possibility of hazardous reactions: Flammable. Reacts with strong oxidizing agents. Toxic fumes may be released if heated above the decomposition point. Used empty containers may contain product gases which form explosive mixtures with air Can form explosive mixtures in air if heated above flash point and/or when sprayed or atout Conditions to avoid: Excessive heat. Incompatible materials: Oxidizers Hazardous decomposition products: Carbon monoxide and carbon dioxide Hydrocarbons Sulfur oxides (SOx) 	
11 Toxicological information	
 Information on toxicological effects Acute toxicity: LD/LC50 values that are relevant for classification: None. Primary irritant effect: On the skin: Slight irritant effect on skin and mucous membranes. On the eye: Slight irritant effect on eyes. Sensitization: Based on available data, the classification criteria are not met. IARC (International Agency for Research on Cancer): 	
8052-42-4 Asphalt	2B
12174-11-7 Attapulgite (Palygorskite)	2B 2B
NTP (National Toxicology Program):	
None of the ingredients are listed.	
· OSHA-Ca (Occupational Safety & Health Administration):	
None of the ingredients are listed.	
 Probable route(s) of exposure: Ingestion. Eye contact. Skin contact. Repeated dose toxicity: Danger of very serious irreversible effects. CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Muta. 1B, Carc. 1B Germ cell mutagenicity: May cause genetic defects. Carcinogenicity: May cause cancer. Reproductive toxicity: Based on available data, the classification criteria are not met. STOT-single exposure: Based on available data, the classification criteria are not met. STOT-repeated exposure: Causes damage to the central nervous system through prolonged or repeated exposure. 	(Contid on posso 0)
	(Cont'd. on page 9)





acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/23/2016

Revision: 03/23/2016

Trade name: Roof Mastic- Rain Kote

(Cont'd. of page 8)

Page: 9/12

· Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

[·] Toxicity

· Aquatic toxicity No relevant information available.

- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- **Mobility in soil:** No relevant information available.
- Ecotoxical effects:
- **Remark:** Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- · Additional ecological information
- · General notes: Avoid release to the environment.
- [·] Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- Other adverse effects: No relevant information available.

13 Disposal considerations

• Waste treatment methods

· Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

[·] Uncleaned packagings

• Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number	
· DOT · ADR, IMDG, IATA	NA1993 Reclassified as combustible under US DOT regulations. Labeling is only required for single packages ≥119 US gal / 450 L to include Combustible symbol and Proper Shipping Name. UN1268
	(Cont'd. on page 10



acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/23/2016

Revision: 03/23/2016

Trade name: Roof Mastic- Rain Kote (Cont'd. of page 9) UN proper shipping name Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 5 L (1.3 gal). COMBUSTIBLE LIQUID, N.O.S (Stoddard Solvent) · DOT · ADR 1268 PETROLEUM DISTILLATES, N.O.S. (STODDARD SOLVENT) · IMDG PETROLEUM DISTILLATES, N.O.S. (STODDARD SOLVENT) ·IATA Petroleum distillates, n.o.s. (Stoddard Solvent) [·] Transport hazard class(es) · DOT · Class 3 Combustible liquids · Label 3 · ADR · Class 3 (F1) Flammable liquids · Label 3 · IMDG, IATA · Class 3 Flammable liquids · Label 3 Packing group · DOT, ADR, IMDG, IATA Ш • Environmental hazards · Marine pollutant: No • Special precautions for user Warning: Flammable liquids · Danger code (Kemler): 30 · EMS Number: F-E,S-E [•] Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. (Cont'd. on page 11)



Printing date: 03/23/2016

Revision: 03/23/2016

Trade name: Roof Mastic- Rain Kote

(Cont'd. of page 10)

[•] Transport/Additional information:

· IATA

Limited quantity by air: 10 L

15 Regulatory information

 Safety, health and mixture United States (USA) SARA 	d environmental regulations/legislation specific for the substance
· Section 355 (extreme	ely hazardous substances):
None of the ingredient	ts are listed.
· Section 313 (Specific	c toxic chemical listings):
None of the ingredient	ts are listed.
· TSCA (Toxic Substa	nces Control Act)
All ingredients are liste	ed.
product as supplied.	
8052-42-4 Asphalt	
12174-11-7 Attapulgit	te (Palygorskite)
	cause reproductive toxicity for females:
None of the ingredient	ts are listed.
	cause reproductive toxicity for males:
None of the ingredient	ts are listed.
	cause developmental toxicity:
None of the ingredient	
· Carcinogenic catego	
· EPA (Environmental	
None of the ingredient	
•	Agency for Research on Cancer):
8052-42-4 Asphalt	2
12174-11-7 Attapulgit	
	Institute for Occupational Safety and Health):
•	
8052-42-4 Asphalt	
8052-42-4 Asphalt • Canadian substance	
8052-42-4 Asphalt • Canadian substance	Substances List (DSL):



acc. to OSHA HCS (29 CFR 1910.1200) and WHMIS 2015 regulations

Printing date: 03/23/2016

Revision: 03/23/2016

Trade name: Roof Mastic- Rain Kote

(Cont'd. of page 11)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

	based on our present knowledge. However, this shall not constitute a guarantee for a atures and shall not establish a legally valid contractual relationship.
Date of preparatio	n / last revision 03/23/2016 / -
IMDG: International Ma DOT: US Department of IATA: International Air CAS: Chemical Abstract LC50: Lethal concentra LD50: Lethal dose, 50 p PBT: Persistent, Bioacc vPvB: very Persistent a NIOSH: National Institu OSHA: Occupational S. Flam. Liq. 3: Flammabl Muta. 1B: Germ cell mu Carc. 1B: Carcinogenict Carc. 2: Carcinogenict STOT RE 1: Specific ta	nent concerning the International Carriage of Dangerous Goods by Road ritime Code for Dangerous Goods f Transportation ransport Association ts Service (division of the American Chemical Society) tion, 50 percent ercent umulative and Toxic nd very Bioaccumulative te for Occupational Safety afety & Health e liquids, Hazard Category 3 tagenicity, Hazard Category 1B ty, Hazard Category 1B ty, Hazard Category 2 rget organ toxicity - Repeated exposure, Hazard Category 1
Sources Website, Europear Website, US EPA overview/home.do) Website, Chemical Patty's Industrial H Casarett and Doul 978-0-07-176923-5	Abstracts Registry, American Chemical Society (www.cas.org) /giene, 6th ed., Rose, Vernon, ed. ISBN: ISBN: 978-0-470-07488-6 's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISB
SDS Prepared by: ChemTel Inc. 1305 North Florida Tampa, Florida US	Avenue A 33602-2902 erica 1-888-255-3924 Intl. +01 813-248-0573