



MATERIAL SAFETY DATA SHEET
BEADEX® All Purpose Drywall Joint Compound

MSDS #61-360-023
 Page 1 of 9

SECTION 1
CHEMICAL PRODUCT AND IDENTIFICATION

United States Gypsum Company
 550 West Adams Street
 Chicago, Illinois 60661-3637
 A Subsidiary of USG Corporation

Product Safety: 1 (800) 507-8899
www.usg.com
 Version Date: January 1, 2008
 Version: 4

PRODUCT(S) | BEADEX® All Purpose Drywall Joint Compound

CHEMICAL FAMILY / GENERAL CATEGORY | Joint Treatment

SYNONYMS | Joint Compound, Taping Compound, Mud

SECTION 2
HAZARD IDENTIFICATION

EMERGENCY OVERVIEW:

CAUTION!

This product is not expected to produce any unusual hazards during normal use. Exposure to high dust levels may irritate the skin, eyes, nose, throat, or upper respiratory tract.

POTENTIAL HEALTH EFFECTS (See Section 11 for more information)

ACUTE :

Inhalation	Exposure to dust generated during the sanding of the product may irritate eyes, skin, nose, throat, and upper respiratory tract. Persons subjected to large amounts of this dust will be forced to leave area because of nuisance conditions such as coughing, sneezing and nasal irritation. Labored breathing may occur after excessive inhalation. If respiratory symptoms persist, consult physician.
------------	---

Eyes	Dust can cause mechanical irritation of eyes. If burning, redness, itching, pain or other symptoms persist or develop, consult physician.
------	---

Skin	None known.
------	-------------

Ingestion	None known.
-----------	-------------

CHRONIC:

Inhalation	Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. The risk of developing silicosis is dependent upon the exposure intensity and duration.
------------	---

Eyes	None known.
------	-------------

Skin	None known.
------	-------------

Ingestion	None known.
-----------	-------------

TARGET ORGANS: Eyes, skin and respiratory system.

PRIMARY ROUTES OF ENTRY: Inhalation, eyes and skin contact.

CARCINOGENICITY CLASSIFICATION OF INGREDIENT(S) All substances listed are associated with the nature of



MATERIAL SAFETY DATA SHEET

BEADEX® All Purpose Drywall Joint Compound

MSDS #61-360-023

Page 2 of 9

the raw materials used in the manufacture of this product and are not independent components of the product formulation. All substances, if present, are at levels well below regulatory limits. See Section 11: Toxicology Information for detailed information.

MATERIAL	IARC	NTP	ACGIH	CAL-65
Vinyl Acetate Monomer	2B	Not Listed	A3	Not Listed
Acetaldehyde	2B	2	A3	Listed
Formaldehyde	1	2	A2	Listed
Crystalline silica	1	1	A2	Listed

IARC - International Agency for Research on Cancer: 1- Carcinogenic to humans; 2A - Probably carcinogenic to humans; 2B - Possibly carcinogenic to humans; 3 - Not classifiable as a carcinogen; 4 - Probably not a carcinogen

NTP - National Toxicology Program (Health and Human Services Dept., Public Health Service, NIH/NIEHS): 1- Known to be carcinogen; 2- Anticipated to be carcinogens

ACGIH - American Conference of Governmental Industrial Hygienists: A1 - Confirmed human carcinogen; A2 - Suspected human carcinogen; A3 - Animal carcinogen; A4 - Not classifiable as a carcinogen; A5 - Not suspected as a human carcinogen

CAL-65 - California Proposition 65 "Chemicals known to the State of California to Cause Cancer"

Respirable crystalline silica: IARC: Group 1 carcinogen, NTP: Known human carcinogen. The weight percent of crystalline silica given represents total quartz and not the respirable fraction. The weight percent of respirable silica has not been measured in this product.

Food and Drug Administration [CFR Title 21, v.3, sec 184.1409] - Ground limestone is Generally Recognized as Safe (GRAS).

POTENTIAL ENVIRONMENTAL EFFECTS: This product has no known adverse effect on ecology. (See Section 12 for more information)

SECTION 3 COMPOSITION, INFORMATION ON INGREDIENTS

MATERIAL	WT%	CAS #
Limestone	>60	1317-65-3
Water	<30	7732-18-5
Attapulgite	<5	12174-11-7
Vinyl Acetate Polymer	<5	9003-20-7
Or Ethylene Vinyl Acetate Polymer		24937-78-8
Crystalline Silica	<2	14808-60-7

All ingredients of this product are included in the U.S. Environmental Protection Agency's Toxic Substances Control Act Chemical Substance Inventory and the Canadian Domestic Substances List (DSL).

The weight percent for silica represents total quartz and not the respirable fraction.

SECTION 4 FIRST AID MEASURES

FIRST AID PROCEDURES

Inhalation	Remove to fresh air. Leave the area of exposure and remain away until coughing and other symptoms subside. Other measures are usually not necessary, however if conditions warrant, contact physician.
Eyes	In case of contact, do not rub or scratch your eyes. To prevent mechanical irritation, flush thoroughly with water for 15 minutes. If irritation persists, consult physician.



MATERIAL SAFETY DATA SHEET

BEADEx® All Purpose Drywall Joint Compound

MSDS #61-360-023

Page 3 of 9

Skin	Wash with mild soap and water. If irritation persists, consult physician.
Ingestion	This product is not intended to be ingested or eaten. If gastric disturbance occurs, call physician.
MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED: Pre-existing upper respiratory and lung diseases such as, but not limited to, bronchitis, emphysema and asthma. Pre-existing skin diseases such as, but not limited to, rashes and dermatitis.	
NOTES TO PHYSICIAN: Treatment should be directed at the control of symptoms and the clinical condition.	

SECTION 5 FIRE FIGHTING MEASURES

General Fire Hazards	None known		
Extinguishing Media	Water or use extinguishing media appropriate for surrounding fire.		
Special Fire Fighting Procedures	Wear appropriate personal protective equipment. See section 8.		
Unusual Fire/Explosion Hazards	None known		
Hazardous Combustion Products	Above 800° C – limestone may decompose to calcium oxide (CaO) and carbon dioxide (CO ₂). Above 175° C – polyvinyl acetate may decompose to H ₂ O, CO ₂ , CO, and acetic acid, could produce vinyl acetate monomers.		
Flash Point	Not Determined	Auto Ignition	Not Applicable
Method Used	Not Applicable	Flammability Classification	Not Applicable
Upper Flammable Limit (UFL)	Not Determined	Rate of Burning	Not Applicable
Lower Flammable Limit (LFL)	Not Determined		

SECTION 6 ACCIDENTAL RELEASE MEASURES

CONTAINMENT: No special precautions. Wear appropriate personal protective equipment. See section 8.
CLEAN-UP: Use normal clean up procedures. No special precautions.
DISPOSAL: Follow all local, state, provincial and federal regulations. Never discharge large releases directly into sewers or surface waters.

SECTION 7 HANDLING AND STORAGE

HANDLING: Avoid dust contact with eyes. Wear the appropriate eye protection against dust (See Section 8). Minimize dust generation and accumulation. Avoid breathing dust. Wear the appropriate respiratory protection against dust in poorly ventilated areas and if TLV is exceeded (see Sections 2 and 8). Use good safety and industrial hygiene practices.



MATERIAL SAFETY DATA SHEET

BEADEX® All Purpose Drywall Joint Compound

MSDS #61-360-023

Page 4 of 9

STORAGE: Store in a cool, dry, ventilated area away from sources of heat, moisture and incompatibilities (see Section 10). Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Close container and discard properly. Keep tightly sealed following use.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

MATERIAL	WT%	TLV (mg/m ³)	PEL (mg/m ³)
Limestone	>60	10	15 (T) / 5 (R)
Water	<30	(NE)	(NE)
Attapulgate	<5	(NE)	(NE)
Vinyl Acetate Polymer	<5	(NE)	(NE)
Or Ethylene Vinyl Acetate Polymer		(NE)	(NE)
Crystalline Silica	<2	0.025 (R)	0.1 (R)

(T)-Total; (R)-Respirable; (NE)-Not Established; (C)-Ceiling; (STEL)-Short-term exposure limit
(F)-Fume; (Du)-Dust; (M)-Mist
ppm-part per million; f/cc-fiber per cubic centimeter; mppcf- million particles per cubic foot

ENGINEERING CONTROLS: Provide ventilation sufficient to control airborne dust levels. If user operations generate airborne dust, use ventilation to keep dust concentrations below permissible exposure limits. Where general ventilation is inadequate, use process enclosures, local exhaust ventilation, or other engineering controls to control dust levels below permissible exposure limits.

RESPIRATORY PROTECTION: Wear a NIOSH/MSHA-approved respirator equipped with particulate cartridges when dusty in poorly ventilated areas, and if TLV is exceeded. A respiratory program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use. If engineering controls are not possible, wear a properly fitted NIOSH/MSHA-approved particulate respirator.

OTHER PERSONAL PROTECTIVE EQUIPMENT:

Eye/Face	Wear eye protection, safety glasses or goggles, to avoid possible eye contact.
Skin	Wear gloves and protective clothing to prevent repeated or prolonged skin contact.
General	Selection of Personal Protective Equipment will depend on environmental working conditions and operations.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Off white	Vapor Density (Air = 1)	< 1(same as water)
Odor	Low to no odor	Specific Gravity (H ₂ O = 1)	1.5 - 1.7
Odor Threshold	Not Determined	Solubility in water (g/100g)	Unlimited dispersibility
Physical State	Paste	Partition Coefficient	Not Determined
pH @ 25 ° C	~ 7.5-11	Auto-ignition Temp	Not Determined
Melting Point	Not Applicable	Decomposition Temp	Not Determined



MATERIAL SAFETY DATA SHEET

BEADEX® All Purpose Drywall Joint Compound

MSDS #61-360-023

Page 5 of 9

Freezing Point	32°F/ 0°C	Viscosity	Not Determined
Boiling Point	212°F/ 100°C	Particle Size	99% Finer than 250 microns
Flash Point	Not Determined	Bulk Density	1.5-1.7 kg/L
Evaporation Rate (BuAc = 1)	Not Determined	Molecular Weight	Mixture
Upper Flammable Limit (UFL)	Not Determined	VOC Content	<2 g/l
Lower Flammable Limit (LFL)	Not Determined	Percent Volatile	20-45
Vapor Pressure (mm Hg)	~24 mmHg@ 25°C		

SECTION 10 CHEMICAL STABILITY AND REACTIVITY

STABILITY	Stable.
CONDITIONS TO AVOID	Contact with incompatibles (see below).
INCOMPATIBILITY	None known.
HAZARDOUS POLYMERIZATION	None known.
HAZARDOUS DECOMPOSITION	Above 800° C – limestone may decompose to calcium oxide (CaO) and carbon dioxide (CO ₂). Above 175° C – polyvinyl acetate may decompose to H ₂ O, CO ₂ , CO, and acetic acid, could produce vinyl acetate monomers.

SECTION 11 TOXICOLOGICAL INFORMATION

ACUTE EFFECTS: None known.

CHRONIC EFFECTS / CARCINOGENICITY:

Vinyl acetate/acetaldehyde/formaldehyde: Ethylene vinyl acetate polymer is a common emulsion polymer most familiar as the component of ordinary white glue which exhibits the "sticky" characteristic. Ethylene vinyl acetate polymer is not classified as a carcinogen by IARC, NTP or ACGIH. Trace amounts of residual vinyl acetate monomers, acetaldehyde and formaldehyde may be associated with the production of ethylene vinyl acetate polymer. Any exposure to vinyl acetate monomer, acetaldehyde, or formaldehyde is expected to remain well below OSHA regulatory and ACGIH recommended limits during normal handling and use of this product.

Crystalline Silica: Exposures to respirable crystalline silica are not expected during the normal use of this product; however, actual levels must be determined by workplace hygiene testing. The weight percent of respirable crystalline silica may not have been measured in this product. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer. The development of silicosis may increase the risks of additional health effects. The risk of developing silicosis is dependent upon the exposure intensity and duration.

In June, 1997, IARC classified crystalline silica (quartz and cristobalite) as a human carcinogen. In making the overall evaluation, the IARC Working Group noted that carcinogenicity in humans was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs.

IARC states that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1).



MATERIAL SAFETY DATA SHEET
BEADEx® All Purpose Drywall Joint Compound

MSDS #61-360-023
 Page 6 of 9

SECTION 12
ECOLOGICAL INFORMATION

ENVIRONMENTAL TOXICITY: This product has no known adverse effect on ecology.

Ecotoxicity value	Not determined.
--------------------------	-----------------

SECTION 13
DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Dispose of material in accordance with federal, state, and local regulations. Never discharge directly into sewers or surface waters. Consult with environmental regulatory agencies for guidance on acceptable disposal practices.

SECTION 14
TRANSPORT INFORMATION

U.S. DOT INFORMATION: Not a hazardous material per DOT shipping requirements. Not classified or regulated.

Shipping Name	Same as product name.
Hazard Class	Not classified.
UN/NA #	None. Not classified.
Packing Group	None.
Label (s) Required	Not applicable.
GGVSec/MDG-Code	Not classified.
ICAO/IATA-DGR	Not applicable.
RID/ADR	None.
ADNR	None.

SECTION 15
REGULATORY INFORMATION

UNITED STATES REGULATIONS

All ingredients of this product are included in the U.S. Environmental Protection Agency's Toxic Substances Control Act Chemical Substance Inventory.



MATERIAL SAFETY DATA SHEET
BEADEX® All Purpose Drywall Joint Compound

MSDS #61-360-023
 Page 7 of 9

MATERIAL	WT%	3 0 2	3 0 4	3 1 3	CERCLA	CAA Sec. 112	RCRA Code
Limestone	>60	NL	NL	NL	NL	NL	NL
Water	<30	NL	NL	NL	NL	NL	NL
Attapulgite	<5	NL	NL	NL	NL	NL	NL
Vinyl Acetate Polymer	<5	NL	NL	NL	NL	NL	NL
Or Ethylene Vinyl Acetate Polymer		NL	NL	NL	NL	NL	NL
Crystalline Silica	<2	NL	NL	NL	NL	NL	NL

Key: NL = Not Listed

SARA Title III Section 302 (EPCRA) Extremely Hazardous Substances: Threshold Planning Quantity (TPQ)

SARA Title III Section 304 (EPCRA) Extremely Hazardous Substances: Reportable Quantity (RQ)

SARA Title III Section 313 (EPCRA) Toxic Chemicals: X= Subject to reporting under section 313

CERCLA Hazardous Substances: Reportable Quantity (RQ)

CAA Section 112 (r) Regulated Chemicals for Accidental Release Prevention: Threshold Quantities(TQ)

RCRA Hazardous Waste: RCRA hazardous waste code

CANADIAN REGULATIONS

This product has been classified in accordance with the hazard criteria of Controlled Product regulations and the MSDS contains all the information required by the Controlled Products Regulations. All ingredients of this product are included in the Canadian Domestic Substances List (DSL).

MATERIAL	WT%	IDL Item #	WHMIS Classification
Limestone	>60	Not Listed	D2A
Water	<30	Not Listed	Not Listed
Attapulgite	<5	Not Listed	Not Listed
Vinyl Acetate Polymer	<5	Not Listed	Not Listed
Or Ethylene Vinyl Acetate Polymer		Not Listed	Not Listed
Crystalline Silica	<2	1406	D2A

IDL Item#: Canadian Hazardous Products Act – Ingredient Disclosure List Item #

WHMIS Classification: Workplace Hazardous Material Information System

Risk and Safety Phrases defined by European Union Directive 67/548/EEC (Annex III and IV)

R-Phrase(s): R36/37/38

S-Phrase(s): S51 S38 S39 S2

**SECTION 16
 OTHER INFORMATION**



MATERIAL SAFETY DATA SHEET

BEADEx® All Purpose Drywall Joint Compound

MSDS #61-360-023
Page 8 of 9

Label Information

⚠ CAUTION!

Dust generated from sanding product may cause irritation to eyes, skin, nose, throat and upper respiratory tract. Avoid irritation by reducing exposure to dust. Use wet-sanding to reduce dust created. Use in a well-ventilated area or provide sufficient local ventilation. If dusty, wear a NIOSH/MSHA-approved respirator. Wear eye protection. If eye contact occurs, flush thoroughly with water for 15 minutes. If irritation persists, call physician. Wash with soap and water after use. Do not ingest. If ingested, call physician. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Close container and discard properly. Product safety information: (800) 507-8899 or www.usg.com.

KEEP OUT OF REACH OF CHILDREN.

INFORMATION FOR HANDLING AND IDENTIFICATION OF CHEMICAL HAZARDS

NFPA Ratings:			HIMS Ratings:		<table border="1"> <tr> <td>HEALTH</td> <td>*</td> <td>1</td> </tr> <tr> <td></td> <td></td> <td>0</td> </tr> <tr> <td>PHYSICAL HAZARD</td> <td></td> <td>0</td> </tr> <tr> <td>PERSONAL PROTECTION</td> <td></td> <td>E</td> </tr> </table>	HEALTH	*	1			0	PHYSICAL HAZARD		0	PERSONAL PROTECTION		E	0 = Minimal Hazard 1 = Slight Hazard 2 = Moderate Hazard 3 = Serious Hazard 4 = Severe Hazard
HEALTH	*		1															
			0															
PHYSICAL HAZARD			0															
PERSONAL PROTECTION		E																
Health:	1	Health:	1															
Fire:	0	Fire:	0															
Reactivity:	0	Reactivity:	0															

E – Safety glasses, gloves and dust respirator

Key/Legend

TLV	Threshold Limit Value
PEL	Permissible Exposure Limit
CAS	Chemical Abstracts Service (Registry Number)
NIOSH	National Institute for Occupational Safety and Health
MSHA	Mine Safety and Health Administration
OSHA	Occupational Health and Safety Administration
ACGIH	American Conference of Governmental Industrial Hygienists
IARC	International Agency for Research on Cancer
DOT	United States Department of Transportation
EPA	United States Environmental Protection Agency
NFPA	National Fire Protection Association
HMIS	Hazardous Materials Identification System
PPE	Personal Protection Equipment
TSCA	Toxic Substances Control Act
DSL	Canadian Domestic Substances List
NDSL	Canadian Non-Domestic Substances List
SARA	Superfund Amendments and Reauthorization Act of 1986
CAA	Clean Air Act
EPCRA	Emergency Planning & Community Right-to-know Act
RCRA	Resource Conservation and Recovery Act
CERCLA	Comprehensive Environmental Response, Compensation and Liability Act of 1980
UN/NA#	United Nations/North America number



MATERIAL SAFETY DATA SHEET

BEADEX® All Purpose Drywall Joint Compound

MSDS #61-360-023
Page 9 of 9

CFR	Code of Federal Regulations
WHMIS	Workplace Hazardous Material Information System
Prepared by: Product Safety USG Corporation 550 West Adams Street Chicago, IL 60661-3637	
The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for his/her own particular use.	
END	

***** SECTION 1: PRODUCT IDENTIFICATION *****
 MANUFACTURERS ADDRESS : 1101 THIRD STREET SOUTH, MINNEAPOLIS, MN 55415
 MFG TELEPHONE NUMBER : (612) 332-7371
 24 HR EMERGENCY PHONE NO : 1-800-228-5635
 CHEMICAL NAME OR FAMILY : PAINT PRODUCT
 TRADE NAME : NOT APPLICABLE
 FORMULA : 07 40239 S/HTG INT S/G BASE 2
 REVISION DATE : 02-06-96
 DATE PRINTED : 09-13-96

***** SECTION 2: HAZARDOUS INGREDIENTS *****

NAME	APPROX WT %	TLV TWA	TLV STEL	OSHA PEL	CEILING	RECORD
COMMON (1): SILICON DIOXIDE	5%	0.10 MG/CU M	NOT ESTAB	0.10 MG/CU M	NOT ESTAB	RECORD NOT ESTAB
CAS: 14808-60-7 CHEMICAL: QUARTZ						
COMMON (NA): TITANIUM DIOXIDE	10%	10.00 MG/CU M	NOT ESTAB	10.00 MG/CU M	NOT ESTAB	RECORD NOT ESTAB
CAS: 13463-67-7 CHEMICAL: TITANIUM OXIDE						

THERE ARE NO SARA 313 CHEMICALS IN THIS PRODUCT
 (1) = THIS MATERIAL IS A CARCINOGEN PER NTP, IARC
 ALL COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH U.S. TSCA CHEMICAL
 SUBSTANCE INVENTORY REQUIREMENTS.

***** SECTION 3: PHYSICAL DATA *****
 BOILING POINT: 212 DEG F
 VAPOR PRESSURE MM HG AT 77 DEG F: 24.0
 VAPOR DENSITY (AIR = 1.0): 7.4
 SPECIFIC GRAVITY (WATER = 1.0): 1.0
 PERCENT VOLATILE: 100
 EVAPORATION RATE (BUTYL ACETATE = 1): .4
 SOLUBILITY IN WATER: YES
 APPEARANCE AND ODOOR: NORMAL FOR A COATINGS PRODUCT.
 THEORETICAL VOC: 1.98 LBS/GALLON
 THEORETICAL VOC: 237 GRAMS/LITER

***** SECTION 4: FIRE AND EXPLOSION HAZARD *****
 FLASH POINT TCC/PM DEG F : 205
 LOWER EXPLOSIVE LIMIT : 2.00
 UPPER EXPLOSIVE LIMIT : 17.00
 EXTINGUISHING MEDIA: CARBON DIOXIDE, DRY CHEMICAL, FOAM, AND/OR WATER FOG.
 SPECIAL FIRE FIGHTING PROCEDURES:
 FIRE FIGHTERS MUST WEAR SELF-CONTAINED BREATHING APPARATUS OR AIR MASKS.
 CONTAINERS EXPOSED TO FIRE SHOULD BE KEPT COOL WITH WATER SPRAY.
 UNUSUAL FIRE AND EXPLOSIVE HAZARDS:
 NONE

***** SECTION 5: HEALTH HAZARD DATA *****
 THRESHOLD LIMIT VALUE: NOT REQUIRED FOR MIXTURE.

EFFECTS OF OVEREXPOSURE:
 IMMEDIATE EFFECTS (ACUTE):
 HARMFUL IF INHALED. MAY AFFECT THE BRAIN, NERVOUS SYSTEM OR RESPIRATORY SYSTEM, CAUSING DIZZINESS, HEADACHE, NAUSEA OR RESPIRATORY IRRITATION.
 CONTAINS STYRENE WHICH IS LISTED BY IAR AS A POSSIBLE HUMAN CARCINOGEN BASED ON ANIMAL DATA. LONG TERM ANIMAL STUDIES NOR HUMAN EPIDEMIOLOGY STUDIES OF WORKERS EXPOSED TO STYRENE PROVIDE AN ADEQUATE BASIS TO CONCLUDE STYRENE IS CARCINOGENIC.
 OVEREXPOSURE TO INGREDIENTS IN THIS PRODUCT MAY CAUSE NOSE AND THROAT IRRITATION, LUNG IRRITATION, EYE IRRITATION, SKIN IRRITATION, HARM IF INHALED, HEADACHE AND NAUSEA, BRONCHITIS OR BRONCHIAL SPASMS.
 DELAYED EFFECTS (CHRONIC):
 CONTAINS INGREDIENTS WHICH MAY CAUSE SKIN IRRITATION.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE - ANY RESPIRATORY OR SKIN CONDITION.
 EMERGENCY AND FIRST AID PROCEDURES:
 NONE

POSSIBLE ROUTES OF ENTRY: INHALATION, INGESTION, SKIN ABSORPTION.
 ***** SECTION 6: REACTIVITY DATA *****

THIS PRODUCT IS STABLE
 CONDITIONS TO AVOID: NONE
 INCOMPATIBILITY: AVOID WATER-REACTIVE MATERIALS.

HAZARDOUS DECOMPOSITION PRODUCTS:
 SILICON DIOXIDE CARBON DIOXIDE/MONOXIDE METAL OXIDES

HAZARDOUS POLYMERIZATION: NONE
 ***** SECTION 7: SPILL OR LEAK PROCEDURES *****
 VENTILATE AREA. REMOVE SPILLS WITH INERT ABSORBENT.

WASTE DISPOSAL METHOD:
 DISPOSE IN CHEMICAL DISPOSAL AREA OR IN A MANNER THAT COMPLIES WITH LOCAL, STATE, AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

***** SECTION 8: SPECIAL PROTECTION INFORMATION *****
 RESPIRATORY PROTECTION:
 UNLESS AIR MONITORING DEMONSTRATES VAPOR/MIST LEVELS ABOVE APPLICABLE LIMITS, NO RESPIRATOR IS REQUIRED. IF RESPIRATOR IS REQUIRED, THE PROTECTIVE EQUIPMENT MUST BE PROPERLY FITTED RESPIRATOR (NIOSH/MSHA APPROVED). SHOULD BE USED ONLY FOR SHORT DURATION APPLICATION. FOLLOW RESPIRATOR MANUFACTURERS DIRECTIONS FOR RESPIRATOR USE.

VENTILATION:
 REQUIRED WHEN SPRAYING OR APPLYING IN CONFINED AREA.
 PROTECTIVE GLOVES: USUAL HAND PROTECTION FOR PAINT APPLICATION.
 EYE PROTECTION: FOR SPRAY APPLICATION, USE CHEMICAL GOGGLES AS A MINIMUM. OTHERWISE, USE SAFETY GLASSES WITH SIDE SHIELDS AS A MINIMUM.
 OTHER PROTECTIVE EQUIPMENT: USUAL CLOTHING FOR PAINTING OPERATIONS.

***** SECTION 9: SPECIAL PRECAUTIONS *****
 PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
 KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STORE ABOVE 120 DEG F. KEEP FROM FREEZING. EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE. DO NOT CUT, PUNCTURE OR MELD CONTAINERS. ALL LABEL MARKINGS MUST BE OBSERVED UNTIL CONTAINER HAS BEEN CLEANED, RECONDITIONED OR PROPERLY DISPOSED OF.

