

n-Propanol

Version 1.00

Revision Date 26.02.2010

1. Identification of the substance/mixture and of the company/undertaking

Trade name	n-Propanol	
Synonyms	n-Propanol, 1-Propanol, Hydrox Propyl alcohol, Ethyl carbinol, r alcohol	
Company	Sasol Solvents A Division of Sasol Chemical Indu Sturdee Avenue 2 ZA 2196 Rosebank	stries
Information (Product safety)	Telephone: +27 11 280 0000 Fax	:: + 27 11 280 0198
Emergency telephone	Europe, Israel, Africa, Americas Middle East, Arabic African countries Asia Pacific China South Africa	+44 (0)208 762 8322 +961 3 487 287 +65 633 44 177 +86 10 5100 3039 +27 (0)17 610 4444



n-Propanol

Version 1.00

Revision Date 26.02.2010

2. Hazards identification

GHS-Classification











n-Propanol

Version 1.00

Revision Date 26.02.2010

Signal word	Danger	
Hazard class	Flammable liquids Acute toxicity Specific target organ toxicity - single exposure Eye damage/irritation Aspiration toxicity	Category 2 Category 4 Category 3 Category 1 Category 2
Hazard statements	H225: Highly flammable liquid and vapour. H302: Harmful if swallowed. H305: May be harmful if swallowed and enters airw. H318: Causes serious eye damage. H336: May cause drowsiness or dizziness.	
Precautionary Statement: Prevention	P210: Keep away from heat/sparks/open flames/hot surfaces No smoking. P233: Keep container tightly closed. P262: Do not get in eyes, on skin, or on clothing. P280: Wear protective gloves/protective clothing/eye protection/face protection.	
Precautionary Statement: Response	 P331: Do NOT induce vomiting. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P350: Gently wash with plenty of soap and water. P313: Get medical advice/attention. 	

3. Composition/information on ingredients

propan-1-ol; n-propanol Contents: 99.90 %W/W

CAS-No. 71-23-8 Index-No. 603-003-00-0 EC-No. 200-746-9 Symbol(s):Flammable,Corrosion,Exclamation Mark,Health Hazard. H-Satements:H225,H302,H305,H318,H336

For the full text of the H-Statements mentioned in this Section, see Section 2.

4. First aid measures

General advice	When symptoms persist or in all cases of doubt seek medical advice.	
Inhalation	Move to fresh air in case of accidental inhalation of vapours. If breathing is irregular or stopped, administer artificial respiration. Call a physician immediately.	
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash	
nt Date 26.02.2010	10000009035	3/7



n-Propanol

ersion 1.00	Revision Date 26.02.2010
	contaminated clothing before re-use. If skin irritation persists, call a physician.
Eye contact	Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician.
Ingestion	If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Suitable extinguishing media	Water spray, Alcohol-resistant foam, Dry chemical, Carbon dioxide (CO2)
Extinguishing media which shall not be used for safety reasons	No information available.
Specific hazards during fire fighting	Flash back possible over considerable distance.
Special protective equipment for fire- fighters	Wear self-contained breathing apparatus and protective suit.
Further information	Cool containers / tanks with water spray.

6. Accidental release measures

Personal precautions	Keep people away from and upwind of spill/leak. Remove all sources of ignition. Do not breathe vapours or spray mist.
Environmental precautions	Should not be released into the environment. Prevent further leakage or spillage if safe to do so.
Methods for cleaning up	Soak up with inert absorbent material and dispose of as hazardous waste.

7. Handling and storage

Handling Safe handling advice	Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Take precautionary measures against static discharge. Ensure all equipment is electrically grounded before beginning transfer operations.	
Advice on protection against fire and explosion	Keep away from heat and sources of ignition. Use explosion- proof equipment.	
Storage		
Print Date 26.02.2010	10000009035	4/7



n-Propanol

Version 1.00

Revision Date 26.02.2010

Requirements for storage Keep containers tightly closed in a dry, cool and well-ventilated place.

8. Exposure controls/personal protection

Components with workplace control parameters

NATIONAL OCCUPATIONAL EXPOSURE LIMITS

Components	Туре	Control parameters	Update	Basis
1-PROPANOL	TWA	491 mg/m3	12 2003	Taiwan OELs
	TWA	200 ppm	12 2003	Taiwan OELs

Engineering measures

Provide sufficient air exchange and/or exhaust in work rooms.

Personal protective equipment

Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Hand protection	Gloves suitable for permanent contact: Material: butyl-rubber Break through time: 4 h Material thickness: 0.5 mm unsuitable gloves Material: Polyvinylchloride, leather, nitrile rubber/nitrile latex, natural rubber/natural latex
Eye protection	Safety glasses with side-shields
Skin and body protection	Protective suit, Safety shoes
Hygiene measures	Wash hands before breaks and immediately after handling the product.
Protective measures	Wear suitable protective equipment.

9. Physical and chemical properties

Form	liquid
state of matter	liquid; at 20 °C; 1,013 hPa
Colour	colourless
Odour	alcohol-like
pН	7



n-Propanol

Version 1.00

Revision Date 26.02.2010

Melting point/range	-126.2 °C
Boiling point/boiling range	97.2 °C
Flash point	26 °C; closed cup
Autoignition temperature	371 °C
Lower explosion limit	2.1 %(V)
Upper explosion limit	13.5 %(V)
Vapour pressure	27.998 hPa; 25 °C
Density	0.805 g/cm3
Water solubility	completely miscible
Viscosity, dynamic	2.170 mPa.s
Relative vapour density	2.1

10. Stability and reactivity

Materials to avoid	Strong oxidizing agents, Incompatible with acids., Halogenated compounds
Hazardous decomposition products	Carbon oxides
Hazardous reactions	Hazardous polymerisation does not occur.

11. Toxicological information

Acute oral toxicity	LD50 rat: 1,870 mg/kg; literature value
Acute inhalation toxicity	LC50 rat: 4,000 mg/l; ; 4 h; literature value
Acute dermal toxicity	LD50 rabbit: 4,060 mg/kg; literature value

12. Ecological information

Ecotoxicity effects	
Toxicity to fish	LC50 Pimephales promelas: 4,480 mg/l; 96 h; literature value

13. Disposal considerations

Product	In accordance with local and national regulations., Do not contaminate ponds, waterways or ditches with chemical or used container., The product should not be allowed to enter drains, water courses or the soil.	
Contaminated packaging	Do not burn, or use a cutting torch on, the empty drum., Triple rinse containers., Can be offered for recycling, re-conditioning	
Print Date 26.02.2010	10000009035	6/7



n-Propanol

Version 1.00

Revision Date 26.02.2010

or puncture.

14. Transport information

ADR	UN-Number: 1274; Class: 3; Packaging group: III; F1; Description of the goods: n-PROPANOL
RID	UN-Number: 1274; Class: 3; Packaging group: III; F1;
	Description of the goods: n-PROPANOL
ADNR	UN-Number: 1274; Class: 3; Packaging group: III; F1;
	Description of the goods: PROPYL ALCOHOL, NORMAL
IMDG	UN-Number: 1274; Class: 3; EmS: F-E, S-D; Packaging group:
	III; Description of the goods: PROPANOL
ICAO/IATA	UN-Number : 1274; Class: 3; Packaging group: III; Description
	of the goods: n-Propanol

15. Regulatory information

Regulatory base	Taiwan CLA GHS Classification List (Council of Labour Affairs,
	GHS documents, July 2009)

16. Other information

All reasonable efforts were exercised to compile this SDS in accordance with ISO 11014 and ANSIZ400.1.1993. The SDS provides information regarding the health, safety and environmental hazards, at the date of issue, to facilitate the safe receipt, use and handling of the product in the workplace. Since Sasol and its subsidiaries cannot anticipate or control all conditions under which the product may be handled, used and received in the workplace, it remains the obligation of each user, receiver or handler to, prior to usage, review this SDS in the context within which the product will be received, handled or used in the workplace. The user, handler or receiver must ensure that the necessary mitigating measures are in place as regards health and safety. This does not substitute the need or requirement for any relevant risk assessments to be conducted. It further remains the responsibility of the receiver, handler or user to communicate such information to all relevant parties that may beinvolved in the receipt, use or handling of the product.

Although all reasonable efforts were exercised in the compilation of this SDS, Sasol does not expressly warrant the accuracy or assume any liability for the incompleteness of the information contained herein or any advice given. The product is sold and risk passes in accordance with the specific terms and conditions of sale.

The MSDS was created by: MOTLATSI The MSDS was approved by: R. Preston